

LOTS 11, 14, 21

0418330
(Page 1 of 8)

INSTALLATION CERTIFICATE

CF-6R

7321 KRISHNA DR
Site Address

Permit Number

An installation certificate is required to be posted at the building site or made available for all appropriate inspections. (The information provided on this form is required; however, use of this form to provide the information is optional.) After completion of final inspection, a copy must be provided to the building department (upon request) and the building owner at occupancy, per Section 10-103(b).

0418330

HVAC SYSTEMS:

Heating Equipment

Equip. Type (pkg. heat pump)	CEC Certified Mfr Name and Model Number	# of Identical Systems	Efficiency (AFUE, etc.) ¹ [CF-1R value]	Duct Location (attic, etc.)	Duct or Piping R-value	Heating Load (Btu/hr)	Heating Capacity (Btu/hr)
SPUT	AA-SAND C05080A945		80	ATTIC	4.2		80K

Cooling Equipment

Equip. Type (pkg. heat pump)	CEC Certified Compressor Unit Mfr Name and Model Number	# of Identical Systems	Efficiency (SEER, etc.) ¹ [CF-1R value]	Duct Location (attic, etc.)	Duct R-value	Cooling Load (Btu/hr)	Cooling Capacity (Btu/hr)
SPUT	FEDDER'S C104201UF		10.0	ATTIC	4.2		42K

1. ≥ reads greater than or equal to.

I, the undersigned, verify that equipment listed above is: 1) the actual equipment installed, 2) equivalent to or more efficient than that specified in the certificate of compliance (Form CF-1R) submitted for compliance with the Energy Efficiency Standards for residential buildings, and 3) equipment that meets or exceeds the appropriate requirements for manufactured devices (from the Appliance Efficiency Regulations or Part 6), where applicable.

12/11/06
Signature, Date

Installing Subcontractor (Co. Name)
OR General Contractor (Co. Name) OR Owner

WATER HEATING SYSTEMS:

Heater Type	CEC Certified Mfr Name & Model Number	Distribution Type (Std. Point-of-Use)	If Recirculation, Control Type	# of Identical Systems	Rated ² Input (kW or Btu/hr)	Tank Volume (gallons)	Efficiency ² (EF, RE)	Standby ² Loss (%)	External Insulation R-value ³
645	STATE GS650YDCTG		N/A		40,000	50	62%	6%	R-16

- 2 For small gas storage (rated input of less than or equal to 75,000 Btu/hr), electric resistance and heat pump water heaters, list Energy Factor. For large gas storage water heaters (rated input of greater than 75,000 Btu/hr), list Recovery Efficiency, Standby Loss and Rated Input.
- 3 R-12 external insulation is mandatory for storage water heaters with an energy factor of less than 0.58.

Faucets & Shower Heads:

All faucets and showerheads installed are certified to the Commission, pursuant to Title 24, Part 6, Section 111.

I, the undersigned, verify that equipment listed above my signature is: 1) the actual equipment installed; 2) equivalent to or more efficient than that specified in the certificate of compliance (Form CF-1R) submitted for compliance with the Energy Efficiency Standards for residential buildings; and 3) equipment that meets or exceeds the appropriate requirements for manufactured devices (from the Appliance Efficiency Regulations or Part 6), where applicable.

Benny K...
Signature, Date

Benny's Plumbing
Installing Subcontractor (Co. Name) OR
General Contractor (Co. Name) OR Owner

COPY TO: Building Department
HERS Provider (if applicable)
Building Owner at Occupancy

INSTALLATION CERTIFICATE

(Page 2 of 13)

CF-6R

MARANATHA CORP

Site Address **ELDER CREEK PARK LOT 11**

Permit Number


FENESTRATION/GLAZING: Plan 1926

Manufacturer/Brand Name	Product U-Factor ¹ (CF-1R value) ²	Product SHGC ¹ (CF-1R value) ²	# of Pairs	Elev. Total Quantity of Like Product (Quantity)	Square Feet	Exterior Shading Device or Overhang	Comments/Location/Special Features
(GROUP LIKE PRODUCTS)							
1. PHILIPS WHITE							
2. VINYL WINDOWS							
3. W/ LOWE2 GLASS							
4.							
5. XO	.35			6	107		
6. SH	.35			1	202		
7. PW	.32			0	0		
8. SGD	.33			1	34		
9.							
10.							
11.							
12.							
13.							
14.							
15.							

¹ Manufactured fenestration products use the values from the product label. Field fabricated fenestration products use the default values from Section 116 of the Energy Efficiency Standards.

² Installed U-Factor must be less than or equal to values from CF-1R. Installed SHGC must be less than or equal to values from CF-1R, or a shading device (exterior or overhang) is installed as specified on the CF-1R. Alternatively, installed weighted average U-Factors for the total fenestration area are less than or equal to values from CF-1R.

I, the undersigned, verify that the fenestration/glazing listed above my signature: 1) is the actual fenestration product installed; 2) is equivalent to or has a lower U-Factor and lower SHGC than that specified in the certificate of compliance (Form CF-1R) submitted for compliance with the *Energy Efficiency Standards* for residential buildings; and 3) the product meets or exceeds the appropriate requirements for manufactured devices (from Part 6), where applicable.

		12/4/06	Sacramento Building Products
Item #s (if applicable)	Signature, Date		Installing Subcontractor (Co. Name) OR General Contractor (Co. Name) OR Owner OR Window Distributor
Item #s (if applicable)	Signature, Date		Installing Subcontractor (Co. Name) OR General Contractor (Co. Name) OR Owner OR Window Distributor
Item #s (if applicable)	Signature, Date		Installing Subcontractor (Co. Name) OR General Contractor (Co. Name) OR Owner OR Window Distributor

COPY TO: Building Department
HERS Provider (if applicable)
Building Owner at Occupancy



OMEGA PRODUCTS INTERNATIONAL, INC.

REPRESENTS THAT

BBF Construction, Inc.

IS AN "APPROVED APPLICATOR" OF THE
DIAMOND WALL ONE-COAT SYSTEM

Omega's approval of this and any other "approved applicator" represents only that Omega has been provided written assurance under penalty of perjury from the Approved Applicator of the Approved Applicator's qualifications to apply Diamond Wall Systems generally, and Omega's Diamond Wall One-Coat System particular. Omega makes no warranty as to the actual skill or qualifications of any such Approved Applicator, and disclaims any responsibility for any actual application of its products or system. Omega Reserve the right to expire this certificate at any time.

Approved this 26th day of December, in the year 2004

Expires this 26th day of December, in the year 2006

Omega Products International, Inc.

Certificate No. 7004

CERTIFICATION OF INSULATION

ADDRESS OR TRACT MARANATHA CORP LOT # 11 ELDER CREEK park #2 Sacto CA 95824			SACRAMENTO BUILDING PRODUCTS <input checked="" type="checkbox"/> PO BOX 864 WEST SACRAMENTO, CA 95811 LIC. #202096 <input type="checkbox"/> 1300 MELODY ROAD, MARYSVILLE, CA 95901 LIC. #202026 <input type="checkbox"/> PO. BOX 9651, FRESNO, CA 93791 9651 LIC. #202026 <input type="checkbox"/> PO BOX 1631 RENO NV 89503 LIC. #10675 <input type="checkbox"/> 3826 A PONDIA-ROSA WAY, LAS VEGAS, NV 89115 LIC. #10176 DATE INSULATION COMPLETED 12-1-06		
WALLS		CEILING		FLOOR	
(SQUARE FEET)		(SQUARE FEET)		(SQUARE FEET)	
TYPE OF INSULATION		TYPE OF INSULATION		TYPE OF INSULATION	
FIBERGLASS		FIBERGLASS		FIBERGLASS	
FORM		FORM		FORM	
BATTS		BATTS & BLOW		BATTS	
MANUFACTURER'S PRODUCT ID		MANUFACTURER'S PRODUCT ID		MANUFACTURER'S PRODUCT ID	
MANUFACTURER		MANUFACTURER		MANUFACTURER	
CT	OC	CT	OC	CT	OC
JM		JM		JM	
R - VALUE INSTALLED	APPLIED THICKNESS	R - VALUE INSTALLED	APPLIED THICKNESS	R - VALUE INSTALLED	APPLIED THICKNESS
13	3 1/2	30	10"		
19	5 1/2	30	12"		
KNEE WALLS IF R-VALUE IS OTHER THAN WALLS ABOVE					
MATERIAL		FORM		MANUFACTURER	
FIBERGLASS		BATTS		CT	OC
				JM	
AIR INFILTRATION SEALANT					
MATERIAL		MATERIAL		MANUFACTURER	
Foam		HILTI		HANDY FOAM	
THIS IS TO CERTIFY THAT INSULATION AND/OR SEALANT HAS BEEN INSTALLED IN CONFORMANCE WITH APPLICABLE CODES, MATERIAL STANDARDS AND REGULATIONS.					
SIGNATURE		TITLE		DATE	
INSULATION CONTRACTOR		MANAGER		12-1-06	
SIGNATURE		TITLE		DATE	
GENERAL CONTRACTOR		JC			
REMARKS					